

MODEL	Rated load Ton	Closed Height	Stroke	Extended Height	Effective Cylinder Area(in <sup>2</sup> )	Oil Capacity in <sup>3</sup>	Plunger Retraction	Working Pressurer	Weight (Lb)
RC-5-SA-3	5	6 1/2"	3"	9 1/2"	0.994	3.2	SPRING	10,060	3
RC-5-SA-5	5	8 1/2"	5"	13 1/2"	0.994	5.2	SPRING	10,060	4
RC-10-SA-1.5	10	3 15/32	1 1/2"	4 31/32"	2.236	3.3	SPRING	8,950	6
RC-10-SA-2	10	4 25/32	2 1/8"	6 29/32"	2.236	4.8	SPRING	8,960	6
RC-10-SA-4	10	6 3/4"	4 1/8"	10 7/8"	2.236	9.2	SPRING	8,960	7
RC-10-SA-6	10	9 3/4"	6 1/8"	15 7/8"	2.236	13.3	SPRING	8,960	12
RC-10-SA-10	10	13 3/4"	10 1/8"	23 7/8"	2.236	22.9	SPRING	8,960	25
RC-20-SA-2	20	3 7/8"	1 3/4"	5 5/8"	4.439	7.7	SPRING	9,030	12
RC-20-SA-6.5	20	10 3/4"	6 5/8"	17 3/8"	4.430	29.4	SPRING	9,030	22
RC-25-SA-6	25	10 3/4"	6 1/4"	17"	5.15	32.2	SPRING	10,185	14
RC-25-SA-14	25	18 3/4"	14 1/4"	33"	5.15	73.5	SPRING	10,185	40
RC-30-SA-2.5	30	4 5/8"	2 7/16"	7 1/16"	6.492	15.8	SPRING	9,250	14
RC-30-SA-6	30	10"	6"	16"	6.492	39.0	SPRING	9,250	27
RC-30-SA-6T	30	10 1/2"	6"	16 1/2"	6.492	39.0	SPRING	9,250	28
RC-30-SA-14	30	19"	14"	33"	6.492	90.9	SPRING	9,250	57
RC-50-SA-2	50	4 27/32"	2 1/8"	6 31/32"	11.045	23.5	SPRING	9,055	25
RC-50-SA-6	50	11"	6 1/8"	17 1/8"	11.045	67.7	SPRING	9,055	50
RC-50-SA-6T	50	11 7/32"	6 1/8"	17 11/32"	11.045	76.7	SPRING	9,055	50
RC-50-SA-14	50	19 3/8"	14"	33 3/8"	11.045	154.6	SPRING	9,055	95
RC-60-SA-3	60	8"	3"	11"	12.56	38	SPRING	9,055	45
RC-60-SA-6	60	11"	6"	17"	12.56	75	SPRING	9,055	57
RC-75-SA-5.5	75	11 1/2"	5 1/2"	17"	15.040	82.7	SPRING	9,975	80
RC-100-S1-2	100	5 3/4"	2"	7 3/4"	20.637	41.3	SPRING	9,695	54
RC-100-SA-6	100	12 1/4"	6"	18 1/4"	20.637	103.2	SPRING	9,695	95