

MODEL	Rated load Ton	Closed Height	Stroke	Extended. Height	Cylinder Area (in)	Oil Capacity In	Plunger Retraction	Working Pressure	Weight (Lb)
RC-□-SA-□	□ □ □/□"	□"	9 1/2"	□.□□	□.□	SPRING	□□□□	□	
RC-□-SA-□	□ □ □/□"	□"	13 1/8"	□.□□	□.□	SPRING	□□□□	□	
RC-□□-SA-□.□	□□ □ □/□	□ //	4 31/32"	□.□□	□.□	SPRING	□□□□	□	
RC-□□-SA-□	□□ 4 25/32	□ □/□"	□ □□/□□"	□.□□	□.□	SPRING	□□□□	□	
RC-□□-SA-□	□□ 6 3/4"	□ □/□"	□□ □/□"	□.□□	□.□	SPRING	□□□□	□	
RC-□□-SA-□	□□ □ □/□"	6 1/8"	□□ □/□"	□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□□	□□ □□ □/□"	10 1/8"	□□ □/□"	□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □ □/□"	□ □/□"	5 5/8"	□.□□	□.□	SPRING	□□□□	□□	
RC-□□-SA-□.□	□□ □□ □/□"	6 5/8"	□□ □/□"	□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □□ □/□"	6 1/4"	□□"	□.□□	□□.□	SPRING	□□□□□	□□	
RC-□□-SA-□□	□□ 18 3/4"	14 1/4"	□□"	□.□□	□□.□	SPRING	□□□□□	□□	
RC-□□-SA-□.□	□□ □ □/□"	□ □/□□"	□ □/□□"	□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □□"	□"	□□"	□.□□	□□	SPRING	□□□□	□□	
RC-□□-SA-□T	□□ 10 y 2"	□"	□□%"	□.□□	□□	SPRING	□□□□	□□	
RC-□□-SA-□□	□□ □□"	□□"	□□"	□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □ □□/□□"	2 1/8"	□ □□/□□"	□□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □□"	6 1/8"	□□□/□"	□□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□T	□□ 11 7/32"	6 1/8"	□□ □□/□□"	□□.□□	□□.□	SPRING	□□□□	□□	
RC-□□-SA-□□	□□ □□ □/□"	□□	33 3/8"	□□.□□	□□□.□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □"	□"	□□"	□□.□□	□□	SPRING	□□□□	□□	
RC-□□-SA-□	□□ □□"	□"	rr	□□.□□	□□	SPRING	□□□□	□□	
RC-□□-SA-□.□	□□ 11 y/	5 1/2"	□□"	□□.□□	□□.□	SPRING	□□□□	□□	
RC-□□□-S□-□	□□□ □ □/□"	□"	□ □/□"	□□.□□	□□.□	SPRING	□□□□	□□	
RC-□□□-SA-□	□□□ □□ □/□"	□"	□□ □/□"	□□.□□	□□□.□	SPRING	□□□□	□□	